



Dimensional Data

Model		ATD 090	ATD 115	ATD 135	ATD 150	ATD 185	ATD 235	ATD 300
Dimensions	L	20	20	20	20	20	23	23
	D	14 3/8	14 3/8	14 3/8	14 3/8	17 3/8	17 5/8	17 5/8
	H	4 3/4	4 3/4	4 3/4	4 3/4	4 3/4	5 3/4	5 3/4
	A	10 3/4	10 3/4	10 3/4	10 3/4	10 3/4	12	12
	B	10 3/4	10 3/4	10 3/4	10 3/4	13 3/4	14	14
	C	4 5/8	4 5/8	4 5/8	4 5/8	4 5/8	5 1/2	5 1/2
	E	2 7/16	2 7/16	2 7/16	2 7/16	2 7/16	2 5/16	2 5/16
F	1 3/16	1 3/16	1 3/16	1 3/16	1 3/16	1 5/16	1 5/16	
Connections (In.)		Inlet OD	3/8	3/8	3/8	3/8	1/2	1/2
		Suction OD	3/8	3/8	3/8	3/8	1/2	1/2
Operating Refrigerant Charge		R 134a (lbs)	0.3	0.5	0.5	0.6	0.8	1.1
Approximate Shipping Weight		(lbs)	12	13	14	16	18	20

Capacity & Electrical Data

Model		ATD 090	ATD 115	ATD 135	ATD 150	ATD 185	ATD 235	ATD 300
Capacity @ BTUH R 134a	1° TD	90	115	135	150	185	235	300
	10° TD	900	1150	1350	1500	1850	2350	3000
	15° TD	1350	1725	2025	2250	2775	3525	4500
FPI		8	8	8	8	8	8	8
Fan Data	No. of Fans	1	1	1	1	1	1	1
	Dia (In.)	6	6	8	8	8	10	10
	CFM	175	165	180	230	365	430	400
Motor Data	RPM	3000	3000	1550	1550	1550	1550	1550
	Amps 115/1/60	0.8	0.8	0.6	0.6	0.6	0.6	0.6
	Motor Heat BTUH	267	267	200	200	200	200	200