



Dimensional Data

| Model | | ETR 155 | ETR 295 | ETR 410 | ETR 455 |
|-------------------------------------|--------------|------------|------------|------------|------------|
| Dimensions | L | 21 1/2 | 35 1/2 | 46 1/2 | 46 1/2 |
| | D | 19 | 19 | 20 1/2 | 20 1/2 |
| | A | 19 1/2 | 33 1/2 | 44 1/2 | 44 1/2 |
| | B | 17 | 17 | 18 1/2 | 18 1/2 |
| Connections (In.) | Inlet OD | 3/8 | 1/2 | 1/2 | 1/2 |
| | Suction OD | 3/8 | 1/2 | 5/8 | 5/8 |
| Operating Refrigerant Charge | R 134a (lbs) | 0.9 | 1.5 | 2.0 | 2.4 |
| Approximate Shipping Weight | (lbs) | 21 | 38 | 48 | 52 |

External equalizer line is 1/4" OD.

Capacity & Electrical Data

| Model | | ETR 155 | ETR 295 | ETR 410 | ETR 455 |
|--------------------------------------|-------------------------|------------|------------|------------|------------|
| Capacity @ 10° TD BTUH R 134a | Evap -20°F ¹ | 1550 | 2950 | 4100 | 4550 |
| | Evap +20°F | 1800 | 3400 | 4750 | 5250 |
| FPI | | 6 | 6 | 6 | 6 |
| Fan Data | No. of Fans | 1 | 2 | 2 | 2 |
| | Dia (In.) | 8 | 8 | 10 | 10 |
| | Total CFM ² | 215 | 430 | 660 | 610 |
| Motor Data | RPM | 3000 | 3000 | 3000 | 3000 |
| | Total Amps: 115/1/60 | 0.82 | 1.64 | 1.64 | 1.64 |
| | 208- 230/1/60 | 0.5 | 1.0 | 1.0 | 1.0 |
| | Total Motor Heat BTUH | 267 | 534 | 534 | 534 |
| Heater Data | Total watts | 550 | 1000 | 1400 | 1400 |
| | Total Amps: 115/1/60 | 4.8 | 8.7 | 12.2 | 12.2 |
| | 230/1/ | 2.4 | 4.4 | 6.1 | 6.1 |

1. For Capacities below -20°F Evaporating Temperature, contact Sales Department.
2. Air flow shown is for frost-free coil.