



ELECTRICAL & CAPACITY DATA

Unit Model	Compressor	BTUH @ 105°F Amb.	Unit MCA			Connections (In.)		Ship Weight (Lbs.)
			208- 230V/360	460V/3/60	575V/3/60	Liquid	Suction	
WCU 5A2	2DC3-050L	77.5	28.9	14.0	10.4	5/8	1 3/8	385
WCU 8A2	2DA3-075L	126.5	41.0	18.6	17.4	5/8	1 3/8	395
WCU 5H2	2DC3-050L	64.3	28.9	14.0	10.4	5/8	1 3/8	425
WCU 8H2	2DA3-075L	106.3	41.0	18.6	17.4	5/8	1 3/8	470
WCU 5M2 ¹	2DC3-050L	52.6	43.9	24.0	20.4	5/8	1 3/8	425
WCU 8M2 ¹	2DA3-075L	88.1	59.6	29.8	28.4	5/8	1 3/8	470
WCU 6L2 ¹	2DA3-060L	36.6	52.0	23.8	22.2	5/8	1 3/8	435
WCU 6L5 ¹	2DA3-060L	42.8	52.0	23.8	22.2	5/8	1 3/8	435

1. With evaporator power supply

Refrigerant charges are in lbs.; R22 for A2, H2, M2, L2 and R404A for L5

Capacities listed;
 A2 @ +40°F SST
 H2 @ +30°F SST
 M2 @ +20°F SST
 L2/L5 @ -20°F SST