



DIMENSIONS, ELECTRICAL & CAPACITY DATA

Unit Model	Compressor	Dimensions (In.)					BTUH ¹ @ 95°F Amb	Unit MCA ²			Connections		Ship Weight (Lbs.)
		L	W	H	A	C		208-230V/360	460V/3/60	575V/3/60	Liquid	Suction	
ACU 6L5	2DA3-060L	80 3/8	40 1/4	44 1/2	42 15/16	38	29.9	55.6	25	23.2	5/8	1 3/8	1240
ACU 8L5	3DB3-075L	80 3/8	40 1/4	44 1/2	42 15/16	38	44.1	59.0	32.3	25.6	5/8	1 3/8	1310
ACU 10L5	3DS3-100L	120 3/8	40 1/4	44 1/2	82 15/16	38	57.8	80.7	36.7	33.8	7/8	1 3/8	1440
ACU 12L5	4DA3-100L	120 3/8	40 1/4	44 1/2	82 15/16	38	62.7	80.7	39.7	34.7	7/8	1 5/8	1510
ACU 15L5	4DL3-150L	120 3/8	40 1/4	44 1/2	82 15/16	38	81.0	99.0	51.3	38.9	7/8	1 5/8	1600
ACU 22L5	4DT3-220L	164	48 1/4	57 1/2	109 3/8	55	96.1	122	63.9	46.5	1 1/8	2 1/8	1800
ACU 29L5	6DL3-270L	164	48 1/4	57 1/2	109 3/8	55	120.2	141	73.1	56.8	1 1/8	2 1/8	1960
ACU 31L5	6DT3-300L	164	48 1/4	57 1/2	109 3/8	55	142.7	159	82.4	65.7	1 1/8	2 1/8	2000

1. Capacity @ -10°F SST

2. With evaporator power supply

Refrigerant charges are in lbs. - R404A