



ELECTRICAL & CAPACITY DATA

Unit Model	Compressor	BTUH @ 105°F Amb.	Unit MCA			Connections (In.)		Ship Weight (Lbs.)
			208- 230V/360	460V/3/60	575V/3/60	Liquid	Suction	
WCU 10A2	3DC3-100L	179.1	55.5	26.0	21.4	7/8	1 3/8	475
WCU 15A2	3DB3-150L	240.0	75.5	37.3	30.3	7/8	1 3/8	490
WCU 10H2	3DC3-100L	151.7	55.5	26.0	21.4	7/8	1 3/8	555
WCU 15H2	3DB3-150L	202.9	75.5	37.3	30.3	7/8	1 3/8	620
WCU 10M2 ¹	3DC3-100L	127.4	75.5	41.0	31.4	7/8	1 3/8	555
WCU 15M2 ¹	3DB3-150L	170.1	95.5	52.3	40.3	7/8	1 3/8	620
WCU 8L2 ¹	3DS3-075L	54.2	55.4	31.1	24.6	7/8	1 3/8	535
WCU 10L2 ¹	3DS3-100L	71.4	73.5	34.3	31.8	7/8	1 3/8	555
WCU 8L5 ¹	3DB3-075L	61.0	55.4	31.1	24.6	7/8	1 3/8	535
WCU 10L5 ¹	3DS3-100L	86.5	73.5	34.3	31.8	7/8	1 3/8	560

1. With evaporator power supply

Refrigerant charges are in lbs.; R22 for A2, H2, M2, L2 and R404A for L5

Capacities listed;
 A2 @ +40°F SST
 H2 @ +30°F SST
 M2 @ +20°F SST
 L2/L5 @ -20°F SST