



DIMENSIONS, ELECTRICAL & CAPACITY DATA

Unit Model	Compressor	BTUH ² @ 105°F Amb.	Unit MCA			Connections (In.)		Ship Weight (Lbs.)
			208- 230V/360	460V/3/60	575V/3/60	Liquid	Suction	
RCU 5A2	2DC3-050L	63.5	28.9	14.0	10.4	5/8	1 3/8	385
RCU 8A2	2DA3-075L	103.1	41.0	18.6	17.4	5/8	1 3/8	395
RCU 5H2	2DC3-050L	50.8	28.9	14.0	10.4	5/8	1 3/8	425
RCU 8H2	2DA3-075L	83.6	41.0	18.6	17.4	5/8	1 3/8	470
RCU 5M2 ¹	2DC3-050L	40.0	43.9	24.0	20.4	5/8	1 3/8	425
RCU 8M2 ¹	2DA3-075L	66.8	59.6	29.8	28.4	5/8	1 3/8	470
RCU 6L2 ¹	2DA3-060L	22.6	52.0	23.8	22.2	5/8	1 3/8	435
RCU 6L5 ¹	2DA3-060L	26.7	52.0	23.8	22.2	5/8	1 3/8	435

1. With evaporator power supply

Refrigerant charges are in lbs.; R22 for A2, H2, M2, L2 and R404A for L5

Capacities listed;
 A2 @ +40°F SST
 H2 @ +30°F SST
 M2 @ +20°F SST
 L2/L5 @ -20°F SST