



Dimensional Data

Model		GMP	GMP	GMP	GMP	GMP	GMP	GMP	GMP	GMP	GMP	GMP
		RMP	RMP	RMP	RMP	RMP	RMP	RMP	RMP	RMP	RMP	RMP
		154	191	215	242	308	382	430	484	573	645	726
Dimensions	L	55	55	55	55	98	98	98	98	141	141	141
	A	44 1/2	44 1/2	44 1/2	44 1/2	87 1/2	87 1/2	87 1/2	87 1/2	130 1/2	130 1/2	130 1/2
	B	-	-	-	-	-	-	-	-	43	43	43
	C	-	-	-	-	43	43	43	43	43	43	43
Connections (In.)	Inlet OD	5/8	7/8	7/8	7/8	7/8	7/8	1 1/8	1 1/8	1 3/8	1 5/8	1 5/8
	Suction OD	1 1/8	1 1/8	1 1/8	1 1/8	1 1/8	1 3/8	1 5/8	1 5/8	1 5/8	1 5/8	2 1/8
	Hot Gas OD	7/8	7/8	7/8	7/8	7/8	7/8	7/8	7/8	7/8	1 1/8	1 1/8
Operating Refrigerant Charge	R 22 (lbs)	5.8	7.8	9.8	11.8	10.9	14.6	18.2	21.9	21.3	26.6	31.9
Approximate Shipping Weight	(lbs)	194	215	238	259	263	387	410	437	548	563	598

GMP models are three pipe hot gas defrost. RMP models are reverse cycle hot gas defrost.
 Hot Gas connection applies to only GMP models
 External equalizer line is 1/4" OD.

Capacity & Electrical Data

Model		GMP	GMP	GMP	GMP	GMP	GMP	GMP	GMP	GMP	GMP	GMP
		RMP	RMP	RMP	RMP	RMP	RMP	RMP	RMP	RMP	RMP	RMP
		154	191	215	242	308	382	430	484	573	645	726
Capacity BTUH @ 10°F TD	Evap. -20°F ¹	15400	19100	21500	24200	30800	38200	43000	48400	57300	64500	72600
	Evap. +20°F ²	17500	21700	24500	27500	35000	43400	49000	55000	65100	73000	82500
FPI		6	6	6	6	6	6	6	6	6	6	6
Fan Data	No. of Fans	1	1	1	1	2	2	2	2	3	3	3
	Dia (In.)	20	20	20	20	20	20	20	20	20	20	20
	Total CFM ³	4130	4060	4020	3980	8260	8120	8040	7950	12180	12060	11940
	Air Throw (ft) ⁴	52	48	46	43	52	48	46	43	48	46	43
Motor Data	RPM	1140	1140	1140	1140	1140	1140	1140	1140	1140	1140	1140
	Amps: 208-230/1/60	4.0	4.0	4.0	4.0	8.0	8.0	8.0	8.0	12.0	12.0	12.0
	208-230/3/60 ⁵	-	-	-	-	6.9	6.9	6.9	6.9	6.9	6.9	6.9
	460/3/60	1.2	1.2	1.2	1.2	2.4	2.4	2.4	2.4	3.6	3.6	3.6
	575/3/60	1.0	1.0	1.0	1.0	2.0	2.0	2.0	2.0	3.0	3.0	3.0
Motor Heat BTUH		2605	2605	2605	2605	5210	5210	5210	5210	7815	7815	7815

- Use with R404A or R507. For capacities below -20°F Evaporating temperature and alternate fin spacing, contact factory.
- Use with R22.
- Air flow shown is for frost free coil.
- Air throw shown is approximate under ideal product stacking conditions.
- 208-230/3/60 units have single phase motors. 2 and 3 motor units are wired in 3-phase configuration.