



DIMENSIONS, ELECTRICAL & CAPACITY DATA

Unit Model	Compressor	Dimensions (In.)					BTUH ² @ 95°F Amb	Unit MCA			Connections		Ship Weight (Lbs.)
		L	W	H	A	B		208- 230V/3/60	460V/3/60	575V/3/60	Liquid	Suction	
ACU 5A2	2DC3-050L	80 3/8	40 1/4	44 1/2	42 15/16	38	55.9	32.5	15.2	11.4	5/8	1 3/8	1220
ACU 8A2	2DA3-075L	80 3/8	40 1/4	44 1/2	42 15/16	38	89.7	44.6	19.8	18.4	5/8	1 3/8	1260
ACU 10A2	3DB3-100L	120 3/8	40 1/4	44 1/2	82 15/16	38	127.7	62.7	28.4	23.4	7/8	1 3/8	1410
ACU 15A2	3DS3-150L	120 3/8	40 1/4	44 1/2	82 15/16	38	170.6	82.7	39.7	32.3	7/8	1 5/8	1520
ACU 20A2	4DA3-200L	120 3/8	40 1/4	44 1/2	82 15/16	38	187.0	91.5	44.7	33.7	7/8	1 5/8	1560
ACU 25A2	4DH3-250L	164	48 1/4	57 1/2	109 9/16	55	239.4	117	59.0	49.2	7/8	2 1/8	1830
ACU 30A2	4DJ3-300L	164	48 1/4	57 1/2	109 9/16	55	278.0	132	66.4	55.3	1 1/8	2 1/8	1920
ACU 35A2	6DH3-350L	229	48 1/4	57 1/2	162	55	337.1	155	77.8	62.0	1 1/8	2 1/8	2400
ACU 40A2	6DJ3-400L	229	48 1/4	57 1/2	162	55	407.8	199	99.7	75.8	1 1/8	2 1/8	2680
ACU 50A2 ¹	8DP1-500L	176	93 1/2	65 1/2	109 9/16	55	491.0	253	127	105	1 3/8	2 5/8	3200
ACU 60A2 ¹	8DS1-600L	176	93 1/2	65 1/2	109 9/16	55	574.0	308	154	112	1 3/8	3 1/8	3500

1. Duplex Units, 4 fans wide
 2. Capacity @ +40°F SST
- Refrigerant charges are in lbs. - R22